

COMMERCIAL BATTERY

RT 5.12-HX (High Voltage)

20.48~61.44kWh



Full automatic manufacturing,
CCS technique



Precise voltage / temperature
/ SOC detection



Top-notch LFP Class A cell
/ Strict capacity grading



Built in WIFI for monitoring and
firmware update



Plug&play wiring cable,
easy installation



LCD display shows
data visually



Modular design, 20-61kWh
flexible configuration

DATASHEET

Model	RT 5.12-H4	RT 5.12-H5	RT 5.12-H6	RT 5.12-H9	RT 5.12-H10
	RT 5.12-H7	RT 5.12-H8		RT 5.12-H11	RT 5.12-H12

Performance

Cell technology	LFP (LiFePO ₄)				
Battery module	5.12 kWh, 51.2 V, 43 kg				
Number of modules	4	5	6	9	10
	7	8		11	12
Battery usable energy [1]	20.48 kWh	25.6 kWh	30.72 kWh	46.08 kWh	51.2 kWh
	35.84 kWh	40.96 kWh		56.32 kWh	61.44 kWh
System Nominal voltage	204.8 V	256 V	307.2 V	460.8 V	512 V
	358.4 V	409.6 V		563.2 V	614.4 V
System Operating voltage	179.2 ~ 224.64 V	224.0 ~ 280.80 V	268.8 ~ 336.96 V	403.2-505.44 V	448.0-561.60 V
	313.6-393.12 V	358.4-449.28 V		492.8-617.76 V	537.6-673.92 V
System Max. continuous charge and discharge current [2]	100 A				

Communication

Display	LCD Display (battery operating status, SOC, alerts, etc.)
Communication	CAN / RS485 / RS232 / Wi-Fi / LAN

General Specification

Dimension (W×D×H)	566×630×1652 mm		566×630×2220 mm		
	22.3×24.8×65.0 inch		22.3×24.8×87.4 inch		
Weight	250 kg (551.2 lbs)	295 kg (650.4 lbs)	340 kg (749.6 lbs)	542.5 kg (1196.0 lbs)	628.5 kg (1385.6 lbs)
	385 kg (848.8 lbs)	430 kg (948.0 lbs)		585.5 kg (1290.8 lbs)	671.5 kg (1480.4 lbs)
Installation	Floor stand				
Operating temperature [3]	Charge : 0 to 50°C (32 to 122°F) Discharge: -15 to 50°C (5 to 122°F)				
Environmental humidity	≤ 95%RH (No condensation)				
Ingress protection rating	IP20				
Warranty Period [4]	10 years				
Scalability	Max. 12 modules per stack, 15 stacks in parallel				
Application	ON Grid / ON Grid + Backup / OFF grid				
Compatible inverters	Refer to compatible inverter list (Compatible with major PCS brands)				

Standard Compliance

Compliance	UN38.3 / IEC62619 / IEC62040-1 / IEC61000-6-2 / IEC61000-6-4 / IEC62477-1 (More available upon request)
------------	---

Ordering and Delivery Parts

Parts	RT-5.12-QC-A (Battery Pack)	
	RT 5.12-H-BCU (Battery Control Unit)	
	RT-R8-A (Battery Rack)	RT-R12-A (Battery Rack)

[1] Test conditions: 100% depth of discharge (DOD), 0.2C rate charge & discharge at 25°C.

[2] There is 0.5C or 1C configurations optional in factory default.

[3] Charge/discharge derating occurs when the temperature is below 0°C or above 45°C.

[4] Please refer to the Warranty Letter for applicable conditions.